## WHAT IS CLAIMED IS:

1. An OLED device comprising a light-emitting layer (LEL) containing a host and an emitting dopant located between a cathode and an anode wherein the dopant is an orange-red light emitting rubrene derivative represented by formula (I):

Formula (I)

## wherein:

- a) there are identical aromatic groups at the 2- and 8-positions;
- b) the phenyl rings in the 5- and 11-positions contain only parasubstituents identical to the aromatic groups in paragraph a); and
  - c) the phenyl rings in the 6- and 12-positions are substituted or not.
- 2. The device of claim 1 comprising a further light-emitting compound to provide a white light emission.
- 3. The device of claim 2 further comprising a blue light-emitting compound to provide a white light emission.

- 4. The device of claim 2 further comprising a filter over-lying the device.
- 5. The device of claim 2 wherein the layer comprises a host and dopant where the dopant is present in an amount of up to 10%-wt of the host.
- 6. The device of claim 5 wherein the dopant is present in an amount of 0.1-5.0%-wt of the host.
- 7. The device of claim 1 wherein the dopant is represented by formula (II):

$$R_1$$
 $(R_2)_n$ 
 $R_1$ 
 $(R_2)_n$ 

Formula (II)

wherein

R<sub>1</sub> is an aromatic carbocyclic or heterocyclic group;

R<sub>2</sub> is a substituent group;

n is 0-5;

provided that all R<sub>1</sub> are the same; and

provided further, that the  $R_2$ , their location and n value on one ring are the same as those on the second ring.

8. The device of claim 1 wherein the dopant is represented by formula (III):

$$(R_3)_m$$
 $(R_2)_n$ 
 $(R_3)_m$ 
Formula (III)

wherein

R<sub>2</sub> and R<sub>3</sub> are independently selected substituent groups;

n and m are independently 0-5;

provided that the R<sub>2</sub>, their location and n value on one ring are the same as those on the second ring; and

provided further, that the  $R_3$ , their location and m value on one ring are the same as those on all rings containing  $R_3$ .

- 9. The device of claim 8 wherein m is 0.
- 10. The device of claim 7 comprising a further light-emitting compound to provide a white light emission.

- 11. The device of claim 10 further comprising a blue light-emitting compound to provide a white light emission.
- 12. The device of claim 10 further comprising a filter over-lying the device.
  - 13. The device of claim 7 wherein  $R_1$  is a phenyl group.
- 14. The device of claim 7 wherein  $R_2$  is located in the meta or para positions of the phenyl group.
  - 15. The device of claim 7 wherein  $R_2$  is fluorine.
  - 16. The device of claim 7 wherein R<sub>2</sub> is a fluorine-containing group.
  - 17. The device of claim 1 wherein the host is an amine compound.
- 18. The device of claim 1 wherein the host comprises N, N'-di-1-naphthalenyl-N, N'-diphenyl-4, 4'-diaminobiphenyl.
- 19. The device of claim 7 wherein the substituents are selected to provide an emitted light having an orange-red hue.
- 20. The device of claim 1 wherein the substituents are selected to provide a reduced loss of initial luminance compared to the device containing no rubrene compound.
- 21. The device of claim 7 wherein R<sub>2</sub> are independently selected from the group consisting of fluorine, fluorine containing groups, alkyl, aryl, alkoxy and aryloxy groups.

- 22. The device of claim 7 wherein the dopant is present in an amount of up to 10%-wt of the host.
- 23. The device of claim 22 wherein the dopant is present in an amount of 0.1-5.0%-wt of the host.
- 24. The device of claim 1 wherein the rubrene derivative is selected from the following:

- 25. An OLED device of claim 1 wherein the rubrene derivative has a wavelength of maximum emission ( $\lambda_{max}$ ) in ethyl acetate solution such that  $560 \text{nm} < \lambda_{max} \le 650 \text{nm}$ .
- 26. An OLED device of claim 25 wherein the rubrene derivative has a wavelength of maximum emission ( $\lambda_{max}$ ) in ethyl acetate solution such that  $565 \text{nm} < \lambda_{max} \le 625 \text{nm}$ .
  - 27. A light-emitting device containing the OLED device of claim 1.
  - 28. A light-emitting display containing the OLED device of claim 1.
- 29. A method of emitting light comprising subjecting the device of claim 1 to an applied voltage.